




CB 1265 HC

B-Qube



Self-contained ice maker - Sprayer system
Daily production up to 140 kg

Hotel
Restaurant
Fast food
Bar
Disco
Fish market
Supermarket
Medical & SPA
Industry



► Position n°



► Features & Plus

- Resistant and crystal cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Adjustable Stainless Steel feet
- Removable and cleanable air filter
- Air cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- ON-OFF rocker switch
- Standard and special voltages
- HFC Free



AISI 304 SS Scotch Brite finish



Adjustable Stainless Steel feet



Removable and cleanable air filter




Easy cleanable internal rounded surfaces



Disappearing insulated door

► Available ice cube size



Cube 23 grams
dimensions H 31.5 x L 32.5

► Prod. 24h

°C	Air temp.		Water temp.		kg	lbs
	10° C	50° F	7° C	45° F	140	309
	21° C	70° F	15° C	60° F	134	295

2 Years Warranty
subject to limitations

► Certifications available for this model



www.bremagroup.it
info@bremaicegroup.it

We are Brema






B-Qube

CB 1265 HC



Self-contained ice maker - Sprayer system
Daily production up to 140 kg



► Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

► Performances

		Water temperature					
		7° C	45° F	15° C	60° F	21° C	70° F
Air temperature	10° C	140 kg					
	50° F		309 lbs				
	21° C			134 kg			
	70° F				295 lbs		
	32° C					122 kg	
	90° F						269 lbs

► Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water in.: 141 mm / 5 9/16" - 290 mm / 11 7/16" - 3/4" ② Water out.: 79 mm / 3 2/16" - 245 mm / 9 10/16" - 24 mm / 15/16"
- ③ Electrical connections: 186 mm / 7 5/16" - 326 mm / 12 13/16"

► Technical information

Production in 24h 140 kg / 309 lbs

Store capacity, up to 65 kg / 143 lbs

Cooling system A -W

Kind of cube Q-23g

Refrigerant R290

Standard voltage 220-240 V ~ 50 Hz

Average power consumption 900 W

Fuse 16 A

Electrical consumption 23 kWh/100kg

Water consumption A: 2 l/kg - 24 gal/100 lbs

W: 17 l/kg - 203 gal/100 lbs

Sizes (L-P-H mm) 840 - 740 - 1075

(L-P-H in) 33 1/16 - 29 2/16 - 42 5/16

Sizes with pack (L-P-H mm) 880 - 785 - 1245

(L-P-H in) 34 10/16 - 30 14/16 - 49

Net weight 113 kg / 249 lbs

Gross weight 133 kg / 293 lbs

Finish AISI 304 stainless steel, scotch brite

All the technical information must be considered at the following conditions:

Sizes without feet

Standard Cube (23 g)

Ambient temperature +21° C

Water temperature +15° C

Electrical consumption at +32° C (standard voltage)

Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 04 - Issued March 2025



www.bremagroup.it
info@bremagroup.it

We are Brema

